



# 1464 | ProfiStar film cutter

Film lifter 1-row version for double ridges



## Artikel-Nummer: 1464



Weight\*: ca. 420 kg



Dimensions\*: 1800 x 1600 x 1450 mm (B x W x H)

### Highlights

- ✓ 1- and 2-row versions
- ✓ Adjustable support wheels
- ✓ Film lifting tools for light soils
- ✓ Film lifting tools for heavy soils
- ✓ Puncture-proof feeler wheels
- ✓ Provides staff economy and efficiency
- ✓ Powder-coated
- ✓ Sturdy construction
- ✓ Partially galvanised

### Art. no.: additional articles

1465	2-row version
1465.01	1-row version
1465.02	light film lifter with interchangeable couler
1465.03	film lifter for heavy soils with interchangeable elements

## ProfiStar film cutter and lifter:

The Metasa film cutter is suitable for 1 or 2 ridges as well as for single and double ridges.

The safe and robust design is absolutely user-friendly.

All cutting elements are assembled in a parallelogram.

Due to the lateral feeler wheels the travelling disc couler always remains centred on the crest of the ridge, even with slight swerves.

As a further work step, the film is then lifted / loosened from the soil and can be taken up completely by a winder.

For this purpose we recommend our Metasa coreless winder (Art. no.: 1404).

The film lifter is suitable for use in accordance with the (StVZO (German Road Traffic Licensing Regulations).

The finish is partially galvanised and powder-coated.

■ ■ ■ Made in Germany

\*Production-related tolerances are possible in the specified data, weights and dimensions. No legally binding assurances of specific properties can be derived from this information. Errors and omissions excepted.

### Suitable for the following crops:

Strawberries

Ridge cultivation

Double ridge