



Article number: 1402

Weight*: approx. 525 kg

Dimensions*: 2500 x 1450 x 1550 mm (b x h x w)

Highlights

- ✓ Unwinding and winding
- ✓ Powder-coated and galvanised version
- ✓ Speed control of the winding motor
- ✓ Hydraulic unwinding brake
- ✓ Provides staff economy and efficiency
- ✓ Protects film, fleece and nets due to clean running mechanism
- ✓ Hydraulic side lift up to 375 mm

Art. no.: additional articles

1039	winding tube Ø 88.9 mm x 1600 mm
1045.12	film winder, complete 1200 mm, winding tube 1750 mm
1045.05	winding tube Ø 88.9 mm x 1750 mm
1045.03	sectional winder plate 800 mm
1045.04	sectional winder plate 1000 mm
1402.02	winding unit
1499	front loader adapter

Wickel Star II film winder with hydraulic drive and side lift. Impressively practical to use.

With the Wickel Star II film winder, you get an efficient combination device that can **unwind and also wind** film. **Innovative and user-friendly is the hydraulic unwinding brake, which can be engaged with the control as required.** Equipped with a powerful hydraulic motor and smartly arranged ball bearings, the winding tubes run smoothly without chatter. The speed control of the winding motor is easy on the film and on the wallet.

Its frame construction is based on sturdy tube and edge profiles. The side lift is equipped with heavy-duty bearing guides and sufficient lubrication points. The two extensions are infinitely adjustable. With the common winding tubes (1600 mm and 1750 mm) the side lift is up to 375 mm.

*Production-related tolerances are possible in the specified data, weights and dimensions. No legally binding assurances of specific properties can be derived from this information. Errors and omissions excepted.

Made in Germany

Suitable for the following crops::

- Strawberries
- Vegetables
- Asparagus
- Onions

#1402_en / Datenblatt_IP // 10-2022 // V1.0